

Amendments to the claims:

1. (currently amended) A drive device of a printing press, having at least two ~~one~~ virtual leading axles axle (a; b) for presetting a desired angular position (Φ_1) of a drive (08) of at least one unit (01; 02; 03; 04; 06; 07) driven by a separate drive motor (M),

wherein the at least two virtual leading axles axle (a; b) ~~is~~ are connected to at least one circuit (15; 20), which is configured to convert chronologically changing datum for the angular position of a leading axle position (Φ) into a pulse train ($I(t)$; $I_0(t)$) in the form of output signals ($I(t)$; $I_0(t)$), wherein the circuit is configured to be parameterized with regard to a number of pulses per rotation ($n/2\pi$) and an assignment to one of the at least two virtual leading axles (a; b).

2. (currently amended) The drive device as recited in claim 1, wherein the pulse train ($I(t)$; $I_0(t)$) is supplied to a drive of a subassembly (19), which is independently driven by the drive (08) of the unit (01; 02; 03; 04; 06; 07) that is coupled to the at least two virtual leading axles axle (a; b).

3. (original) The drive device as recited in claim 1, wherein the circuit includes a number of subcircuits that are able to generate a number of pulse trains ($I(t)$) in the form of output signals ($I(t)$) at a number of outputs.

4. (previously presented) The drive device as recited in claim 3, wherein the circuit (15; 20) or subcircuit is adjustable with regard to additional parameters ($n/2\pi$, τ , I , $I_n(t)$, "0") that relate to a shape of the output signal ($I(t)$).
5. (previously presented) The drive device as recited in claim 3, wherein the circuit (15; 20) or subcircuit is embodied in the form of an emulator circuit.
6. (previously presented) The drive device as recited in claim 3, wherein the input of the circuit (15; 20) or subcircuit receives the current leading axle position (Φ) from a drive control unit (13) or a computing and data processing unit (11) of the printing press.
7. (original) The drive device as recited in claim 1, wherein the circuit (15; 20) is connected as a client to a network (09) that conveys the leading axle position (Φ) and receives its angular position at its input.
8. (original) The drive device as recited in claim 1, wherein a drive control unit (13) that presets the leading axle position (Φ) is provided, which has at least one circuit (15; 20).

9. (previously presented) The drive device as recited in claim 1, wherein a first and at least one second circuit (20; 15) are provided for converting the chronologically changing datum for the angular position of a leading axle position (Φ) into a pulse train ($I(t)$; $I_0(t)$) in the form of output signals ($I(t)$; $I_0(t)$).

10. (currently amended) The drive device as recited in claim 9, wherein a drive control unit (13; 17) that presets the leading axle position (Φ) has a first circuit (20), which converts the chronologically changing datum of the leading axle position (Φ) into a first pulse train ($I_0(t)$) with a fixed, definite number of pulses per rotation ($n/2\pi$) of the at least two virtual leading axles axle (a; b).

11. (original) The drive device as recited in claim 10, wherein an output of the first circuit (20) communicates with the input of a second circuit (15), which is able to convert the first pulse train ($I_0(t)$) into a new pulse-shaped output signal ($I(t)$) in conjunction with parameters ($n/2\pi$, τ , I , $I_n(t)$, "0") that influence the shape.

12. (previously presented) The drive device as recited in claim 11, wherein the second circuit (15) has a number of subcircuits, which are able to generate a number of different pulse trains ($I(t)$) in the form of output signals ($I(t)$) at a number of outputs.

13. (previously presented) The drive device as recited in claim 11, wherein the parameters ($n/2\pi$, τ , I , $I_n(t)$, "0") of the circuit (15) or its subcircuits are adjustable.

14. (currently amended) The drive device as recited in claim 1, wherein it is possible to parameterize the output signal ($I(t)$) with regard to the number of output pulses per rotation ($n/2\pi$) of the at least two virtual leading axles axle (a; b).

15. (previously presented) The drive device as recited in claim 1, wherein it is possible to parameterize the circuit (15; 20) with regard to the number of pulses per rotation ($n/2\pi$) of a subassembly (19) to be controlled by means of the circuit (15; 20).

16. (previously presented) The drive device as recited in claim 4, wherein it is possible to parameterize the output signal ($I(t)$) with regard to a height of its amplitude (I).

17. (previously presented) The drive device as recited in claim 1, wherein the converted pulse train ($I(t)$) is present at the output of the circuit (15; 20) in the form of a digital output signal ($I(t)$).

18. (previously presented) The drive device as recited in claim 1,

wherein the converted pulse train ($I(t)$) is present at the output of the circuit (15; 20) in the form of an analog output signal ($I(t)$).

19. (previously presented) The drive device as recited in claim 1, wherein the output signal ($I(t)$) at an output has a set of correlated pulse trains ($I_A(t)$; $I_B(t)$; $I_C(t)$).

20. (previously presented) The drive device as recited in claim 4, wherein the circuit (15; 20) is detachably connected to a computing unit (11) in order to adjust the parameters ($n/2\pi$, τ , I , $I_n(t)$, "0").

21. (original) The drive device as recited in claim 1, wherein the leading axle position (Φ) is preset by a drive control unit (13; 17).

22. (currently amended) The drive device as recited in claim 10, wherein the drive control unit (13; 17) that presets the leading axle position (Φ) is embodied in the form of an independent master for the drives (08) that are coupled to the at least two virtual ~~this~~ leading axles axle (a; b).

23. (previously presented) The drive device as recited in claim 10, wherein the drive control unit (17) that presets the leading axle position (Φ) is embodied as a drive control unit (17) of a folding unit (06).

24. (currently amended) A method for controlling a subassembly of a printing press having at least ~~two~~ one virtual leading ~~axles~~ axle (a; b) for presetting a desired angular position (Φ_1') of a drive (08) of at least one unit (01; 02; 03; 04; 06; 07) driven by a separate drive motor (M),

wherein at least one circuit (15; 20) connected to the at least two virtual leading axles axle (a; b) converts the chronologically changing datum for the angular position of a leading axle position (Φ) into a pulse train ($I(t)$; $I_0(t)$) and supplies it in the form of output signals ($I(t)$; $I_0(t)$) to the subassembly (19) and an incremental resolution between the rotating leading axle (a; b) and an angular position transducer of a subassembly (19) to be controlled via the circuit (15; 20) or its drive motor is performed by parameterizing the circuit with regard to a number of pulses per rotation ($n/2\pi$) and an assignment to one of the at least two virtual leading axles (a; b).